



07/17/00

JC877 U.S. PTO

09/618044



07/17/00

UTILITY PATENT APPLICATION TRANSMITTAL <small>(Only for new nonprovisional applications under 37 CFR 1.53(b))</small>	Attorney Docket No.	9350-0169-0
	First Inventor or Application Identifier	Werner POMPETZKI
	Title	PROCESS FOR HYDROGENATION OF ACETONE

APPLICATION ELEMENTS See MPEP chapter 600 concerning utility patent application contents	ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231
1. <input checked="" type="checkbox"/> Fee Transmittal Form (e.g. PTO/SB/17) <small>(Submit an original and a duplicate for fee processing)</small> 2. <input checked="" type="checkbox"/> Specification Total Pages 13 3. <input checked="" type="checkbox"/> Drawing(s) (35 U.S.C. 113) Total Sheets 2 4. <input checked="" type="checkbox"/> Oath or Declaration Total Pages 4 a. <input checked="" type="checkbox"/> Newly executed (original or copy) b. <input type="checkbox"/> Copy from a prior application (37 C.F.R. §1.63(d)) <small>(for continuation/divisional with box 15 completed)</small> i. <input type="checkbox"/> DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §1.63(d)(2) and 1.33(b). 5. <input type="checkbox"/> Incorporation By Reference <small>(usable if box 4B is checked)</small> The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4B, is considered to be part of the disclosure of the accompanying application and is hereby incorporated by reference therein.	ACCOMPANYING APPLICATION PARTS 6. <input checked="" type="checkbox"/> Assignment (executed)/Form PTO-1595 (3 pp.) 7. <input type="checkbox"/> 37 C.F.R. §3.73(b) Statement <input type="checkbox"/> Power of Attorney <small>(when there is an assignee)</small> 8. <input type="checkbox"/> English Translation Document <small>(if applicable)</small> 9. <input checked="" type="checkbox"/> Information Disclosure Statement (IDS) <input checked="" type="checkbox"/> Copies of IDS Citations (5) 10. <input type="checkbox"/> Preliminary Amendment 11. <input checked="" type="checkbox"/> White Advance Serial No. Postcard 12. <input type="checkbox"/> Small Entity Statement(s) <input type="checkbox"/> Statement filed in prior application. Status still proper and desired. 13. <input checked="" type="checkbox"/> Certified Copy of Priority Document (1) <small>(if foreign priority is claimed)</small> 14. <input checked="" type="checkbox"/> Other: Request for Priority; Form PTO-1449
15. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below: <input type="checkbox"/> Continuation <input type="checkbox"/> Divisional <input type="checkbox"/> Continuation-in-part (CIP) of prior application no.: Prior application information: Examiner: Group Art Unit:	
16. Amend the specification by inserting before the first line the sentence: <input type="checkbox"/> This application is a <input type="checkbox"/> Continuation <input type="checkbox"/> Division <input type="checkbox"/> Continuation-in-part (CIP) of application Serial No. Filed on <input type="checkbox"/> This application claims priority of provisional application Serial No. Filed	
17. CORRESPONDENCE ADDRESS <div style="text-align: center;"> 22850 (703) 413-3000 FACSIMILE: (703) 413-2220 </div>	

Name:	Norman F. Oblon	Registration No.:	24,618
Signature:	<i>F.D. Vastine</i>	Date:	7/17/00
Name:	Frederick D. Vastine, Ph.D.	Registration No.:	27,013

TITLE OF THE INVENTION

PROCESS FOR THE HYDROGENATION OF ACETONE

BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention relates to a process for the hydrogenation of acetone to give isopropanol.

Description of the Background

Acetone is a large-volume industrial product and can be prepared in specific ways, e.g. by oxidation of propane, or as a coproduct in the Hook phenol synthesis.

10 In the Hook phenol synthesis, one molecule of acetone is obtained per molecule of phenol. The demand for phenol is very different from that for acetone. For example, phenol and acetone are consumed in a ratio of 2:1 in the synthesis of bisphenol A.

A possible downstream product of acetone is isopropanol which has a significantly broader range of use. A very significant proportion of the isopropanol is converted into ethers, in particular diisopropyl ether and tert-butyl isopropyl ether.

15 The conversion of acetone into isopropanol is generally conducted by catalytic hydrogenation. For the production of isopropanol ethers, processes of hydrogenation and etherification are combined. Thus, EP 0 694 518, EP 0 665 207, EP 0 652 200 and EP 0 661 257 disclose processes for preparing various isopropyl ethers. The disclosures of these patent applications involve the following process sequence:

- a) Catalytic hydrogenation of an acetone-containing liquid phase.
- b) Etherification of the resulting isopropanol over acid catalyst systems.

20 The process steps a) and b) are conducted one after the other, i.e. without work-up of the product mixture obtained from a).

25 Furthermore, EP 0 665 207 teaches a single-stage process in which a) and b) are

conducted by means of a suitable combination catalyst in a single reactor. Because of by-product formation (the processes are designed for the preparation of isopropyl ether), isolation of the isopropanol after the reaction step a) is very costly.

The process described in EP 0 379 323 is a better method of preparing isopropanol from acetone. In this process, acetone is catalytically hydrogenated at a temperature of from 20 to 200°C at pressures of from 1 to 80 bar using, as a matter of necessity, a trickle reactor. Trickle reactors are used in order to create a high mass transfer area between liquid and gas. They therefore have to have a trickle surface having a large surface area. The quality of the isopropanol obtained and the amount of by-products is not discussed.

For many applications, isopropanol must not contain by-products such as isopropyl ether nor traces of solvent from the hydrogenation of acetone. This is particularly true in the case where isopropanol is used in medical and cosmetic applications for the preparation of downstream products where isopropanol of a very high degree of purity is required. High degrees of purity can be achieved on an industrial scale only upon the implementation of costly purification steps. Thus, for example, when isopropanol is prepared by introduction of water into propane, sulfur-containing compounds which are present in the isopropanol product can prevent its use in the cosmetic or pharmaceutical industry. Removal of these contaminating components is only possible by further treatment of the isopropanol with activated carbon, Al_2O_3 or metals such as copper or nickel. A need continues to exist for a method of producing higher purity isopropanol by the hydrogenation of acetone.

Summary of the Invention

Accordingly, one object of the present invention is to provide a process for more efficiently hydrogenating acetone to yield highly pure isopropanol.

Briefly, this object and other objects of the present invention as hereinafter will become more readily apparent can be attained by a process for preparing isopropanol of high purity, which comprises:

hydrogenating acetone in the liquid-phase in at least two hydrogenation process stages, thereby preparing isopropanol product.

Brief Description of the Drawings

A more complete appreciation of the invention and many of the attendant advantages thereof will be readily obtained as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings, wherein:

Figure 1 is a schematic diagram of the invention showing the hydrogenation of acetone in two reactors which are a circulation reactor and a shaft oven; and

Figure 2 is a schematic diagram showing the batchwise hydrogenation of acetone.




Detailed Description of the Preferred Embodiments

It has now been surprisingly found that acetone can be hydrogenated in a multistage process to give isopropanol product of high purity.

The process of the invention can be used for the industrial-scale preparation (> 100,000 metric tons per annum) of isopropanol from acetone. The formation of by-products is virtually completely avoided so that complicated post-reaction processing is unnecessary.

The present invention accordingly provides a process for the hydrogenation of acetone to isopropanol product, wherein hydrogenation is conducted by liquid-phase hydrogenation in at least two stages.

The following reactions can occur in the hydrogenation of acetone:



After the alkali-catalyzed aldol condensation a) of acetone to diacetone alcohol (DAA), elimination of water leads to 4-methyl-3-penten-2-one (mesityl oxide, MOX). The hydrogenation of the intermediate MOX leads via 4-methyl-2-pentanone (methyl isobutyl ketone, MIBK) to 4-methyl-2-pentanol (MPOL). However, DAA can also be hydrogenated directly to hexylene glycol (HG). The desired product IPA can also react further with elimination of water b) to form the undesired diisopropyl ether (DIPE).

A suitable catalyst for the reaction should, if possible, be one which functions under neutral reaction conditions so that it does not catalyze the undesirable secondary reaction of IPA, the aldol condensation and the subsequent elimination of water.

Some of the abovementioned secondary reactions proceed with elimination of water. In order to suppress these secondary reactions, i.e. in order to increase selectivity, the addition of a small amount of water is therefore conceivable. This addition of water, which is undesirable in some specific uses of the isopropanol, remains in the product mixture and may have to be removed.

In contrast, the present invention makes it possible to hydrogenate acetone containing a very small amount of water. This is all the more surprising, since in the abovementioned literature, an addition of water to the feed stream is necessary in order to increase selectivity or to reduce by-product formation.

In the process of the invention, acetone having a water content of less than or equal to 1.0% by weight, preferably less than or equal to 0.5% by weight, very particularly preferably 0.2% by weight can be hydrogenated to form isopropanol.

The high conversions sought in industrial-scale processes can in the present case be achieved either by means of circulation reactors or reactors in cascade connected in series.

The multistage process of the invention enables acetone to be hydrogenated to give isopropanol of high purity. The individual, parallel and/or cascade process stages can be configured as circulation reactors or tube reactors.

The reaction conditions can be varied within wide limits. That is; the liquid-phase hydrogenation can be conducted at a temperature of 60 to 140°C, preferably 70 to 130°C, and a pressure of 20 to 50 bar, preferably 25 to 35 bar. The temperature and pressure conditions can differ in the various process stages.

In general, an excess of hydrogen is employed; the molar ratio of hydrogen to acetone

09616044-071700

ranging from 1.5:1 to 1:1.

In a specific embodiment of the process of the invention, the hydrogenation reaction is conducted in two process stages where the reactor of the 1st process stage is configured as a circulation reactor and the reactor of the 2nd process stage is configured as a tube reactor.

5 A simplified flow diagram of an embodiment of the process of the invention together with a few optional components is shown in Fig. 1.

The flow scheme shows upstream circulation reactor A with the ability to recycle product. The conversion which occurs here is a major part of the required hydrogenation conversion. Reactor A operates at a high concentration level and can be operated using a small circulation ratio. The product from the circulation reactor can then be subjected to intermediate cooling in apparatus component (B). The hydrogenation in the final conversion step is conducted in a shaft oven (C) which operates as a tube reactor without product recirculation. The hydrogen feed and discharge lines are denoted by a) and the product line is denoted by p). Both reactors A and C are designed as adiabatic reactors.

10 The starting temperature of the first process stage is advantageously ranges from 50 to 90°C and the total pressure ranges from 10 to 30 bar. If the catalyst has a high initial activity, it is possible either to reduce the starting temperature or to increase the circulation ratio in the first reactor so as to be able to set the outlet temperature to correspond to the inlet temperature of the second reactor.

20 The reactor of the first process stage can be operated as a circulation reactor with a circulation ratio ranging from 6 to 10. The concentration of acetone in the circulating stream drops by from 8 to 20% by weight while the concentration of isopropanol increases by the

corresponding amount. The hydrogenation reaction is exothermic so that cooling should be provided in or downstream of the circulation reactor. The liquid-phase hydrogenation of the first process stage can be conducted at a temperature ranging from 60 to 130°C, preferably from 80 to 120°C, and a pressure ranging from 20 to 50 bar, preferably from 25 to 35 bar.

5 The second process stage, which is operated with the characteristics of a tube reactor, can be conducted at a temperature ranging from 60 to 140°C, preferably from 70 to 130°C, and a pressure ranging from 20 to 50 bar.

10 The same hydrogenation catalyst can be used in the different process stages. Suitable catalysts include commercial hydrogenation catalysts comprising Cu, Cr, Ru or Ni as the active component on a Al_2O_3 , TiO_2 or ZrO_2 support. In the process of the invention, nickel-containing catalysts, e.g. comprising about 10% by weight of nickel on a neutral support, have been found to be useful.

15 The support material for the catalyst should in all cases be neutral. Neutral support materials include, for example, $\alpha\text{-Al}_2\text{O}_3$, TiO_2 , ZrO_2 and mullite.

20 The process of the invention provides isopropanol of high purity. The total concentration of the by-products formed in the hydrogenation, e.g. 4-methyl-3-penten-2-one, 4-methyl-2-pentanol, diacetone alcohol, hexylene glycol and diisopropyl ether, can be less than 300 ppm, preferably less than 200 ppm, very particularly preferably less than 100 ppm.

25 The multistage reactor concept offers further advantages because of its high flexibility. Circulation ratio, pressure and temperature can be set independently in the reactors. Should the catalyst activity in a reactor decrease, it is possible, for example, to allow a correspondingly higher temperature in the next reactor.

When designing the reactors, good liquid distribution or a high gas exchange area should be ensured. This can be achieved by means of a suitable liquid distributor, e.g. Raschig rings, wire mesh or Sulzer mixers, and a sufficiently high throughput per unit cross-sectional area (viz. linear velocity) of at least $30 \text{ m}^3/\text{m}^2\cdot\text{h}$.

5 Having now generally described this invention, a further understanding can be obtained by reference to certain specific examples which are provided herein for purposes of illustration only and are not intended to be limiting unless otherwise specified.

Example:

An experimental plant as shown in Fig. 2 was set-up.

10 In batchwise experiments, starting material F is allowed to flow into separation vessel A and is pumped around the circuit of the scheme and in the process by-passes reactor R. The apparatus including the reactor is subsequently brought to the desired reaction conditions. At the commencement of the reaction, appropriated switches are turned so as to permit the flow of material in the circuit to flow the reactor R. After about 5 minutes, constant temperature and pressure have become established and the first product samples are taken. Hydrogen is
15 introduced into the reactor and is discharged from the system via lines H and G, respectively. Using different suitable catalyst weights in the reactor, the pump circulation of material yields product at different conversions on a single pass through the catalyst bed of the reactor. Furthermore, isothermal operation is guaranteed, which simplifies the kinetic evaluation of the
20 experiments. Taking samples at various times during the experiment enables a concentration-contact time curve to be recorded. Such experiments correspond to the reactor engineering model of a discontinuously operated stirred tank or a tube reactor.

A nickel-containing catalyst (10% by weight of nickel) on a neutral α -Al₂O₃ support was used.

Experimental results:

Circulation reactor of the 1st process stage:

5	Inlet temperature	70°C	
	Outlet temperature	115°C	
	Circulation ratio	1:8	
	Linear velocity	220 m/h	
	Percent by weight at inlet		Percent by weight at outlet
10	Acetone	22.2	12.5
	Isopropanol	77.8	87.5

Tube reactor of the 2nd process stage:

	Inlet temperature	70°C	
	Outlet temperature	126°C	
15	Linear velocity	38 m/h	
	Percent by weight at inlet		Percent by weight at outlet
	Acetone	12.5	0.54
	Isopropanol	87.5	99.45
	By-products		<100 ppm

By-products of the hydrogenation reaction include: methyl isobutyl ketone, 4-methyl-2-pentanol, hexylene glycol and other high-boilers whose identities were not determined.

The disclosure of German priority application Serial Number 199 33 691.1 filed July 17, 1999 is hereby incorporated by reference into the present application.

Obviously, numerous modifications and variations of the present invention are possible in light of the above teachings. It is therefore to be understood that within the scope of the appended claims, the invention may be practiced otherwise than as specifically described herein.

What Is Claimed As New And Is Intended To Be Secured By Letters Patent Is:

1. A process for the hydrogenation of acetone, which comprises:
conducting the liquid-phase hydrogenation of acetone in at least two hydrogenation
process stages, thereby preparing isopropanol product.

5 2. The process as claimed in claim 1, wherein the liquid-phase hydrogenation in a first
stage is conducted at a temperature of 60 to 140°C and a pressure of 20 to 50 bar.

3. The process as claimed in claim 1, wherein, in the product isopropanol which is
formed, the total concentration of the by-products which are formed does not exceed 300 ppm.

10 4. The process as claimed in claim 1, wherein the acetone to be hydrogenated has a water
content of less than or equal to 1.0% by weight.

5. The process as claimed in claim 4, wherein the acetone to be hydrogenated has a water
content of less than or equal to 0.5% by weight.

6. The process as claimed in claim 5, wherein the acetone to be hydrogenated has a water
content of less than or equal to 0.2% by weight.

7. The process as claimed in claim 1, wherein the liquid-phase hydrogenation reaction is conducted in the presence of a nickel containing catalyst on a neutral support.

8. The process as claimed in claim 7, wherein said neutral support is α -Al₂O₃.

9. The process as claimed in claim 2, wherein the liquid-phase hydrogenation is
5 conducted at a temperature of 70 to 130°C, and a pressure of 25 to 35 bar.

10. The process as claimed in claim 1, wherein the liquid-phase hydrogenation in a second stage is conducted at a temperature of 60 to 140°C, and a pressure ranging from 20 to 50 bar. 70 to 130°C.

11. The process as claimed in claim 10, wherein the liquid-phase hydrogenation is
10 conducted at a temperature of 70 to 130°C.

12. The process as claimed in claim 1, wherein the hydrogenation is conducted at a molar ratio of hydrogen to acetone ranging from 1.5:1 to 1:1.

Abstract of the Disclosure

Acetone is hydrogenated by a process comprising, conducting the liquid-phase hydrogenation of acetone in at least two hydrogenation process stages, thereby preparing isopropanol product with a high selectivity and in high purity.

09618044.071700

5

I:\atty\FDV\93500169.pa.wpd




FIGURE 1




FIGURE 2

Declaration and Power of Attorney for Patent Application

Erklärung für Patentanmeldungen mit Vollmacht

German Language Declaration

Als nachstehend benannter Erfinder erkläre ich hiermit an
Eides Statt:

As a below named inventor, I hereby declare that:

daß mein Wohnsitz, meine Postanschrift und meine Staatsangehörigkeit den im nachstehenden nach meinem Namen aufgeführten Angaben entsprechen, daß ich nach bestem Wissen der ursprüngliche, erste und alleinige Erfinder (falls nachstehend nur ein Name angegeben ist) oder ein ursprünglicher, erster und Miterfinder (falls nachstehend mehrere Namen aufgeführt sind) des Gegenstandes bin, für den dieser Antrag gestellt wird und für den ein Patent für die Erfindung mit folgendem Titel beantragt wird:

My residence, post office address and citizenship are as stated next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

PROCESS FOR THE HYDROGENATION OF

ACETONE

deren Beschreibung:

the specification of which:

☐ ist beigelegt

☒ is attached hereto.

☐ wurde angemeldet am _____

☐ was filed on _____

unter der US-Anmeldenummer oder unter der Internationalen Anmeldenummer im Rahmen des Vertrags über die Zusammenarbeit auf dem Gebiet des Patentwesens (PCT)

as United States Application Number or PCT International Application Number

_____ und am _____

_____ and was amended on _____

_____ abgeändert (falls zutreffend).

_____ (if applicable).

Ich bestätige hiermit, daß ich den Inhalt der oben angegebenen Patentanmeldung, einschließlich der Ansprüche, die eventuell durch einen oben erwähnten Zusatzantrag abgeändert wurde, durchgesehen und verstanden habe.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

Ich erkenne meine Pflicht zur Offenbarung jeglicher Informationen an, die zur Prüfung der Patentfähigkeit in Einklang mit Titel 37, Code of Federal Regulations, § 1.56 von Belang sind.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56.

German Language Declaration

Ich beanspruche hermit ausländische Prioritätsvorteile gemäß Title 35, US-Code, § 119(a)-(d), bzw. § 365(b) aller unten aufgeführten Auslandsanmeldungen für Patente oder Erfindurkunden, oder § 365(a) aller PCT internationalen Anmeldungen, welche wenigstens ein Land ausser den Vereinigten Staaten von Amerika benennen, und habe nachstehend durch ankreuzen sämtliche Auslandsanmeldungen für Patente bzw. Erfindurkunden oder PCT internationale Anmeldungen angegeben, deren Anmeldetag dem der Anmeldung, für welche Priorität beansprucht wird, vorangeht.

Prior foreign application(s)
(Frühere ausländische Anmeldungen)

19933691.1	GERMANY
(Number) (Nummer)	(Country) (Land)
(Number) (Nummer)	(Country) (Land)

Ich Beanspruche hiermit Prioritätsvorteile unter Title 35, US-Code, § 119(e) aller US-Hilfsanmeldungen wie unten aufgezählt.

(Application No.) (Aktenzeichen)	(Filing Date) (Anmeldetag)

Ich beanspruche hiermit die mir unter Title 35, US-Code, § 120 zustehenden Vorteile aller unten aufgeführten US-Patentanmeldungen bzw. § 365(c) aller PCT internationalen Anmeldungen, welche die Vereinigten Staaten von Amerika benennen, und erkenne, insofern der Gegenstand eines jeden früheren Anspruchs dieser Patentanmeldung nicht in einer US-Patentanmeldung, bzw. PCT internationalen Anmeldung in in einer gemäß dem ersten Absatz von Title 35, US-Code, § 112 vorgeschriebenen Art und Weise offenbart wurde, meine Pflicht zur Offenbarung jeglicher Informationen an, die zur Prüfung der Patentfähigkeit in Einklang mit Title 37, Code of Federal Regulations, § 1.56 von Belang sind und die im Zeitraum zwischen dem Anmeldetag der früheren Patentanmeldung und dem nationalen oder im Rahmen des Vertrags über die Zusammenarbeit auf dem Gebiet des Patentwesens (PCT) gültigen internationalen Anmeldetags bekannt geworden sind.

(Application No.) (Aktenzeichen)	(Filing Date) (Anmeldetag)

(Application No.) (Aktenzeichen)	(Filing Date) (Anmeldetag)

Ich erkläre hiermit, daß alle in der vorliegenden Erklärung von mir gemachten Angaben nach bestem Wissen und Gewissen der Wahrheit entsprechen, und ferner daß ich diese falsche Erklärungen in Kenntnis dessen abgebe, daß wissenschaftlich und vorsätzlich falsche Angaben oder dergleichen gemäß § 1001, Title 18 des US-Code strafbar sind und mit Geldstrafe und/oder Gefängnis bestraft werden können und daß derartige wissenschaftlich und vorsätzlich falsche Angaben die Rechtswirksamkeit der vorliegenden Patentanmeldung oder eines aufgrund deren erteilten Patentes gefährden können.

I hereby claim foreign priority under Title 35, United States Code, § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below, and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priorität claimed

Priorität beansprucht

17/July/1999	XXX	
(Day/Month/Year Filed) (Tag/Monat/Jahr der Anmeldung)	Yes Ja	No Nein
	<input type="checkbox"/> Yes Ja	<input type="checkbox"/> No Nein
(Day/Month/Year Filed) (Tag/Monat/Jahr der Anmeldung)		

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below.

(Application No.) (Aktenzeichen)	(Filing Date) (Anmeldetag)

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

(Status) (patented, pending, abandoned) (Status) (patentiert, schwebend, aufgegeben)	

(Status) (patented, pending, abandoned) (Status) (patentiert, schwebend, aufgegeben)	

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

German Language Declaration

VERTRETUNGSVOLLMACHT: Als benannter Erfinder beauftrage ich hiermit den (die) nachstehend aufgeführten Patentanwalt (Patentanwälte) und/oder Vertreter mit der Verfolgung der vorliegenden Patentanmeldung sowie mit der Abwicklung aller damit verbundenen Angelegenheiten vor dem US-Patent- und Markenamt. (Name(n) und Registrationsnummer(n) auflisten)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: (list name and registration number)

Norman F. Oblon, Reg. No. 24,618; Marvin J. Spivak, Reg. No. 24,913; C. Irvin McClelland, Reg. No. 21,124; Gregory J. Maier, Reg. No. 25,599; Arthur I. Neustadt, Reg. No. 24,854; Richard D. Kelly, Reg. No. 27,757; James D. Hamilton, Reg. No. 28,421; Eckhard H. Kuesters, Reg. No. 28,870; Robert T. Pous, Reg. No. 29,099; Charles L. Gholz, Reg. No. 26,395; William E. Beaumont, Reg. No. 30,996; Robert F. Gnuse, Reg. No. 27,295; Jean-Paul Lavelleye, Reg. No. 31,451; Stephen G. Baxter, Reg. No. 32,884; Robert W. Hahl, Reg. No. 33,893; Richard L. Treanor, Reg. No. 36,379; Steven P. Wehrhouch, Reg. No. 32,829; John T. Goolkasian, Reg. No. 26,142; Richard L. Chinn, Reg. No. 34,305; Steven E. Lipman, Reg. No. 30,011; Carl E. Schlier, Reg. No. 34,426; James J. Kulbaski, Reg. No. 34,848; Richard A. Neifeld, Reg. No. 35,299; J. Derek Mason, Reg. No. 35,270; Surinder Sachar, Reg. No. 34,423; Christina M. Gadano, Reg. No. 37,628; Jeffrey B. McIntyre, Reg. No. 36,867; Paul E. Rauch, Reg. No. 38,591; William T. Enos, Reg. No. 33,128 and Michael E. McCabe, Jr., Reg. No. 37,182, with full powers of substitution and revocation.

Postanschrift

Send Correspondence to:

OBLON, SPIVAK, McCLELLAND, MAIER & NEUSTADT, P.C.
FOURTH FLOOR
1755 JEFFERSON DAVIS HIGHWAY
ARLINGTON, VIRGINIA 22202 U S A

Telefonische Auskünfte
(Name und Telefonnummer)

Direct Telephone calls to (name and telephone number)

(703) 413-3000

Vor- und Zuname des einzigen oder ersten Erfinders	Full name of sole or first inventor Werner POMPETZKI	
Unterschrift des Erfinders	Datum:	Inventor's signature <i>Werner Pompetzki</i> 22.05.2000
Wohnsitz	Residence 46284 Dorsten, GERMANY	
Staatsangehörigkeit	Citizenship GERMANY	
Postanschrift	Post Office Address Hellweg 156 a	
	46284 Dorsten, GERMANY	
Vor- und Zuname des zweiten Miterfinders (falls zutreffend)	Full name of second joint inventor, if any Joachim SCHULER	
Unterschrift des zweiten Erfinders	Datum:	Second inventor's signature <i>Joachim Schuler</i> 22.05.2000
Wohnsitz	Residence 45772 Marl, GERMANY	
Staatsangehörigkeit	Citizenship GERMANY	
Postanschrift	Post Office Address Bitterfelder Strasse 2	
	45772 Marl, GERMANY	

(Im Falle dritter und weiterer Miterfinder sind die entsprechenden Informationen und Unterschriften hinzuzufügen)

(Supply similar information and signature for third and subsequent joint inventors)

German Language Declaration

Vor- und Zuname des dritten Miterfinders (falls Zutreffend)		Full name of third joint inventor, if any	
		Dietrich MASCHMEYER	
Unterschrift des dritten Erfinders	Datum	Third inventor's signature	Date
		<i>Dietrich Maschmeyer</i>	22 May 2000
Wohnsitz		Residence	
		45657 Recklinghausen, GERMANY	
Staatsangehörigkeit		Citizenship	
		GERMANY	
Postanschrift		Post Office Address	
		Wickingstrasse 5 a	
		45657 Recklinghausen, GERMANY	
Vor- und Zuname des vierten Miterfinders (falls Zutreffend)		Full name of fourth joint inventor, if any	
Unterschrift des vierten Erfinders	Datum	Fourth inventor's signature	Date
Wohnsitz		Residence	
Staatsangehörigkeit		Citizenship	
Postanschrift		Post Office Address	
Vor- und Zuname des fünften Miterfinders (falls Zutreffend)		Full name of fifth joint inventor, if any	
Unterschrift des fünften Erfinders	Datum	Fifth inventor's signature	Date
Wohnsitz		Residence	
Staatsangehörigkeit		Citizenship	
Postanschrift		Post Office Address	
Vor- und Zuname des sechsten Miterfinders (falls Zutreffend)		Full name of sixth joint inventor, if any	
Unterschrift des sechsten Erfinders	Datum	Sixth inventor's signature	Date
Wohnsitz		Residence	
Staatsangehörigkeit		Citizenship	
Postanschrift		Post Office Address	

(Im Falle dritter und weiterer Miterfinder sind die entsprechenden Informationen und Unterschriften hinzuzufügen.)

(Supply similar information and signature for third and subsequent joint inventors.)